



PRESSURE WASHER

11-May-07

Code: **LD20HHPB-A00Z** SKU **05019** Model: **Pressure Washer, 2000PSI/3GPM**

GENERAL FEATURES

Pressure: 2000 PSI
 Flow Rate: 3.0 GPM
 Cleaning Units: 6000 CU
 Pressure Hose: 50 Feet - 3/8", 4000psi
 Pressure Gun: 4000PSI/7GPM
 Nozzle Size: 4
 Nozzle Quantity/Type: 5 Quick Couple
 Tires: 10" Pneumatic

Features	Thermal Relief	Yes	Hourmeter	No
	Chemical Injector	Yes	Pressure Gauge	Opt
	Safety Relief	Opt	Flow Gauge	Opt
	Low Oil Protection	Yes		
	Easy-Start Valve	No		

Referring conditions are DIN6271, altitude 100 m over see level, temperature 27°C, humidity 60%.

ENGINE

Brand: Honda
 Model: GX 160
 Stroke: 4 cycle
 No. and cylinder disposition: 1 inclined
 Cubic cc.: cc 163
 Aspiration: Natural
 Cooling system: Air
 Starting system: Recoil
 Rpm: rpm 3600
 Continuous HP DIN6270B: HP 4.4
 Power DIN70020: HP 5.5
 Oil capacity: Litres 0.60 Quarts 0.63
 Max water capacity: Litres 0.00 Quarts 0.00
 Fuel consumption @ 4/4 load: Litres/h 1.38 Gal/h 0.37
 Fuel type: Gasoline
 Electric system voltage: Volt 0

PUMP

Brand: Annovi Reverberi
 Model: XTV 3G20D
 Type: Triplex Plunger Pump
 Standard revolutionary speed: rpm 3400
 Flow: gpm 3.0
 Pressure: psi 2000
 Unloader Valve Model: Minimatic 4/B
 Coupling Type: 3/4" Hollow
 Mounting Flange: F7

OVERALL DIMENSIONS AND WEIGHT

Length: mm 756 in 29.75
 Width: mm 559 in 22
 Height: mm 483 in 19
 Weight: Kg 29.48 Lbs 65.0
 Fuel tank capacity: Litres 3.70 Gal 0.98
 Run Time: h 2.7
 Noise level at 7 mts: dB(A) 0.0

THIS DOCUMENT IS PROPERTY OF PRAMAC INDUSTRIES, INC. ALL RIGHTS RESERVED.
Information contained on this document is believed to be correct but is not guaranteed.



PRESSURE WASHER

11-May-07

Code: **LD30HHPB-A00Z** SKU **05020** Model: **Pressure Washer, 3000PSI/3GPM**

GENERAL FEATURES

Pressure: **3000** PSI
 Flow Rate: **3.0** GPM
 Cleaning Units: **9000** CU
 Pressure Hose: **50** Feet - **3/8"**, **4000psi**
 Pressure Gun: **4000PSI/7GPM**
 Nozzle Size: **4**
 Nozzle Quantity/Type: **5 Quick Couple**
 Tires: **10" Pneumatic**

Features	Thermal Relief	Yes	Hourmeter	No
	Chemical Injector	Yes	Pressure Gauge	Opt
	Safety Relief	Opt	Flow Gauge	Opt
	Low Oil Protection	Yes		
	Easy-Start Valve	No		

Referring conditions are DIN6271, altitude 100 m over see level, temperature 27°C, humidity 60%.

ENGINE

Brand: **Honda**
 Model: **GX 270**
 Stroke: **4 cycle**
 No. and cylinder disposition: **1 inclination angle**
 Cubic cc.: **cc 270**
 Aspiration: **Natural**
 Cooling system: **Air**
 Starting system: **Recoil**
 Rpm: **rpm 3600**
 Continuous HP DIN6270B: **HP 7.5**
 Power DIN70020: **HP 9**
 Oil capacity: **Litres 1.10** **Quarts 1.16**
 Max water capacity: **Litres 0.00** **Quarts 0.00**
 Fuel consumption @ 4/4 load: **Litres/h 2.38** **Gal/h 0.63**
 Fuel type: **Gasoline**
 Electric system voltage: **Volt 0**

PUMP

Brand: **Annovi Reverberi**
 Model: **GXMV 4G30A**
 Type: **Triplex Plunger Pump**
 Standard revolutionary speed: **rpm 3400**
 Flow: **gpm 3.0**
 Pressure: **psi 3000**
 Unloader Valve Model: **Gymatic 3/B**
 Coupling Type: **Tapered**
 Mounting Flange: **F35**

OVERALL DIMENSIONS AND WEIGHT

Length: **mm 1067** **in 42**
 Width: **mm 610** **in 24**
 Height: **mm 660** **in 26**
 Weight: **Kg 59.87** **Lbs 132.0**
 Fuel tank capacity: **Litres 6.02** **Gal 1.59**
 Run Time: **h 2.5**
 Noise level at 7 mts: **dB(A) 0.0**

THIS DOCUMENT IS PROPERTY OF PRAMAC INDUSTRIES, INC. ALL RIGHTS RESERVED.
Information contained on this document is believed to be correct but is not guaranteed.



PRESSURE WASHER

11-May-07

Code: **LD35HHPB-A00Y** SKU **05021** Model: **Pressure Washer, 3500PSI/4GPM**

GENERAL FEATURES

Pressure: **3500** PSI
 Flow Rate: **4.0** GPM
 Cleaning Units: **14000** CU
 Pressure Hose: **50** Feet - **3/8"**, 4000psi
 Pressure Gun: **4500PSI/8GPM**
 Nozzle Size: **4**
 Nozzle Quantity/Type: **5** Quick Couple
 Tires: **10" Pneumatic**

Features	Thermal Relief	Yes	Hourmeter	No
	Chemical Injector	Yes	Pressure Gauge	Opt
	Safety Relief	Opt	Flow Gauge	Opt
	Low Oil Protection	Yes		
	Easy-Start Valve	No		

Referring conditions are DIN6271, altitude 100 m over see level, temperature 27°C, humidity 60%.

ENGINE

Brand: **Honda**
 Model: **GX 390**
 Stroke: **4 cycle**
 No. and cylinder disposition: **1 inclination angle**
 Cubic cc.: **cc 389**
 Aspiration: **Natural**
 Cooling system: **Air**
 Starting system: **Recoil**
 Rpm: **rpm 3600**
 Continuous HP DIN6270B: **HP 10.5**
 Power DIN70020: **HP 13**
 Oil capacity: **Litres 1.10** Quarts **1.16**
 Max water capacity: **Litres 0.00** Quarts **0.00**
 Fuel consumption @ 4/4 load: **Litres/h 3.34** Gal/h **0.88**
 Fuel type: **Gasoline**
 Electric system voltage: **Volt 0**

PUMP

Brand: **Annovi Reverberi**
 Model: **GRKV 4G35H**
 Type: **Triplex Plunger Pump**
 Standard revolutionary speed: **rpm 3400**
 Flow: **gpm 4.0**
 Pressure: **psi 3500**
 Unloader Valve Model: **Gymatic 3/B**
 Coupling Type: **Tapered**
 Mounting Flange: **F35**

OVERALL DIMENSIONS AND WEIGHT

Length: **mm 1067** **in 42**
 Width: **mm 610** **in 24**
 Height: **mm 660** **in 26**
 Weight **Kg 72.58** **Lbs 160.0**
 Fuel tank capacity: **Litres 6.51** **Gal 1.72**
 Run Time: **h 2.0**
 Noise level at 7 mts: **dB(A) 0.0**

THIS DOCUMENT IS PROPERTY OF PRAMAC INDUSTRIES, INC. ALL RIGHTS RESERVED.
Information contained on this document is believed to be correct but is not guaranteed.